



Energy of the Future, Today

Global: +86 571-56260008

AU: +61 1300 476529
DE: +49 (0) 6142 4091664

UK: +44 2476 586998
NED: +31 (0) 852 737932

 www.solaxpower.com
 info@solaxpower.com



SOLAX STRING INVERTER

ENGINEERED FOR SOLAR

Product Brochure



X1 SINGLE PHASE INVERTER

SolaX X1 single phase inverters are high quality single & dual MPPT inverters offering efficiency and reliability at an unbeatable cost.

SolaX have developed a range of single phase inverters, unrivaled in the industry for their quality, reliability and efficiency. The SolaX single phase inverters boast a wide MPPT voltage range to allow you to harvest the maximum amount of energy possible from your PV system and have a maximum input voltage of 600V, with a maximum efficiency up to 97.8%.

SolaX Power Network Technology(Zhejiang) Co., Ltd is one of the largest inverter manufacturer in China, a subsidiary company of Hangzhou Sunny Energy Science & Technology Co., Ltd. SolaX established in 2010. Headquarter located in the National College Science Park of Zhejiang University, to cooperate with Zhejiang University, focusing on research and development of Photovoltaic products.

Specialized in R&D, production, sales and service by a range of grid-tied inverters, PV Storage inverters and Family Smart Energy systems. So far, SolaX is one of few domestic Photovoltaic manufacturers offering massive production of smart PV Storage inverters.

SolaX has achieved more than 50 national patents including 15 invention patents, 25 utility model patents, and more than 10 design patents. SolaX inverters also have been tested and obtained more than 120 international authorized certifications.





X1-MINI (SINGLE PHASE)

X1-0.7 X1-1.1 X1-1.5 X1-2.0

INPUT (DC)				
Max.PV array power [Wp]	1050	1650	2250	3000
Max.DC voltage [V]	400	400	400	400
Nominal DC operating voltage [V]	360	360	360	360
Max. input current [A]	12	12	12	12
Max. short circuit current [A]	14	14	14	14
MPPT voltage range[V]	55-380	55-380	55-380	55-380
Start operating voltage[V]	70	70	70	70
No. of MPPT trackers	1	1	1	1
Strings per MPPT tracker	1	1	1	1
OUTPUT AC				
Nominal AC power [VA]	700	1100	1500	2000
Max. AC power [VA]	770	1210	1650	2200
Nominal grid voltage(AC voltage range) [V]	220/230/240; 180~280			
Nominal grid frequency/range [Hz]	50/60; ±5			
Nominal AC current [A]	3.04	4.78	6.52	8.70
Max. AC current [A]	3.3	5.3	7.2	9.6
Displacement power factor	0.8 leading ~ 0.8 lagging			
THDi, rated power [%]	<3			
EFFICIENCY				
MPPT efficiency [%]	99.9			
Euro efficiency [%]	95	95.5	96	96.5
Max. efficiency [%]	97.1			
POWER CONSUMPTION				
Standby consumption (Night) [W]	<1			
STANDARD				
Over voltage protection	YES			
Over current protection	YES			
DC isolation impedance monitoring	YES			
Ground fault current monitoring	YES			
DC injection monitoring	YES			
RCD protection	YES			
Safety	IEC62109-1/-2			
EMC	EN61000-6-1;EN61000-6-2;EN61000-6-3;EN61000-3-2;EN61000-3-3			
Certification	G98; AS4777; VDE4105; EN50549; CEI0-21			
ENVIRONMENT LIMIT				
Degree of protection(according to IEC60529)	IP65			
Operating temperature range [°C]	-25~+60(derating at 45)			
Max. operation altitude [m]	<2000			
Humidity [%]	0~100 (condensation)			
Storage temperature [°C]	-25~+60			
Typical noise emission [dB]	<25			
DIMENSION AND WEIGHT				
Dimensions(WxHxD) [mm]	267*328*116			
Weight[kg]	6			
Cooling concept	Natural			
Topology	Non-isolated			
Communication interfaces	Pocket WiFi(optional)/Pocket LAN(optional)/Pocket GPRS(optional)/Meter(optional)/RS485/DRM/USB-Upgrade			
LCD display	Yes			
Standard warranty [years]	5-10			



X1-AIR (SINGLE PHASE)

X1-2.5 X1-3.0 X1-3.3

INPUT (DC)			
Max.PV array power [Wp]	3750	4500	4950
Max.DC voltage [V]	600	600	600
Nominal DC operating voltage [V]	360	360	360
Max. input current [A]	12	12	12
Max. short circuit current [A]	14	14	14
MPPT voltage range[V]	70-580	70-580	70-580
Start operating voltage[V]	80	80	80
No. of MPPT trackers	1	1	1
Strings per MPPT tracker	1	1	1
OUTPUT AC			
Nominal AC power [VA]	2500	3000	3300
Max. AC power [VA]	2750	3300	3630
Nominal grid voltage(AC voltage range) [V]	220/230/240; 180~280		
Nominal grid frequency/range [Hz]	50/60; ±5		
Nominal AC current [A]	10.9	13.0	14.3
Max. AC current [A]	12.0	14.3	15.8
Displacement power factor	0.8 leading ~ 0.8 lagging		
THDi, rated power [%]	<2		
EFFICIENCY			
MPPT efficiency [%]	99.9		
Euro efficiency [%]	96.8		
Max. efficiency [%]	97.1		
POWER CONSUMPTION			
Standby consumption (Night) [W]	<1		
STANDARD			
Over voltage protection	YES		
Over current protection	YES		
DC isolation impedance monitoring	YES		
Ground fault current monitoring	YES		
DC injection monitoring	YES		
RCD protection	YES		
Safety	EN62109-1/-2		
EMC	EN61000-6-2;EN61000-6-3;EN61000-3-2;EN61000-3-3		
Certification	G98;AS4777;VDE4105; EN50549; CEI0-21		
ENVIRONMENT LIMIT			
Degree of protection(according to IEC60529)	IP65		
Operating temperature range [°C]	-25~+60(derating at 45)		
Max. operation altitude [m]	<2000		
Humidity [%]	0~100 (condensation)		
Storage temperature [°C]	-25~60		
Typical noise emission [dB]	<25		
DIMENSION AND WEIGHT			
Dimensions(WxHxD) [mm]	323*402*119		
Weight[kg]	10.5		
Cooling concept	Natural		
Topology	Non-isolated		
Communication interfaces	Pocket WiFi(optional)/Pocket LAN(optional)/Pocket GPRS(optional)/Meter(optional)/RS485/DRM/USB-Upgrade		
LCD display	Yes		
Standard warranty [years]	5-10		



X1-BOOST (SINGLE PHASE)

	X1-3.0T	X1-3.3T	X1-3.6T	X1-4.2T	X1-4.6T	X1-5.0T
INPUT (DC)						
Max.PV array power [Wp]	4500	4950	5400	6300	6900	7500
Max.recommended DC power[W]	A:3300 B:3300	A:3300 B:3300	A:3300 B:3300	A:3300 B:3300	A:3300 B:3300	A:3300 B:3300
Max.DC voltage [V]	600	600	600	600	600	600
Nominal DC operating voltage [V]	360	360	360	360	360	360
Max. input current [A]	12/12	12/12	12/12	12/12	12/12	12/12
Max. short circuit current [A]	14/14	14/14	14/14	14/14	14/14	14/14
MPPT voltage range[V]	70-580	70-580	70-580	70-580	70-580	70-580
Start operating voltage[V]	100	100	100	100	100	100
No. of MPPT trackers/Strings per MPPT tracker	2(1/1)	2(1/1)	2(1/1)	2(1/1)	2(1/1)	2(1/1)
OUTPUT AC						
Nominal AC power [VA]	3000	3300	3680	4200	4600	5000 (4600 for VDE4105)
Max. AC power [VA]	3300	3630	4048 (3680 for G98)	4620	5060	5500 (4600 for VDE4105)
Nominal grid voltage(AC voltage range) [V]	220/230/240; 180~280					
Nominal grid frequency/range [Hz]	50/60; ±5					
Nominal AC current [A]	13	14.3	16	18.3	20	21.7 (20 for VDE4105)
Max. AC current [A]	14.3	15.8	17.6(16 for G98)	20.1	22	23.9 (20 for VDE4105) (21.7for AS4777)
Displacement power factor	0.8 leading ~ 0.8 lagging					
THDi, rated power [%]	<2					
EFFICIENCY						
MPPT efficiency [%]	99.9					
Euro efficiency [%]	97.0					
Max. efficiency [%]	97.8					
POWER CONSUMPTION						
Standby consumption (Night) [W]	<0.5					
STANDARD						
Over voltage protection	YES					
Over current protection	YES					
DC isolation impedance monitoring	YES					
Ground fault current monitoring	YES					
DC injection monitoring	YES					
RCD protection	YES					
Safety	IEC62109-1/-2					
EMC	EN 61000-6-1 / EN 61000-6-2 / EN 61000-6-3					
Certification	VDE4105 /G98 / G99/ AS4777 / EN50549 / CEI0-21					
ENVIRONMENT LIMIT						
Degree of protection(according to IEC60529)	IP65					
Operating temperature range [°C]	-25~+60(derating at 45)					
Max. operation altitude [m]	<2000					
Humidity [%]	0~100 (condensation)					
Storage temperature [°C]	-25~+60					
Typical noise emission [dB]	<25					
DIMENSION AND WEIGHT						
Dimensions(WxHxD) [mm]	341.5*430*143					
Weight[kg]	13.5	13.5	13.5	14.5	14.5	14.5
Cooling concept	Natural					
Topology	Non-isolated					
Communication interfaces	Pocket WiFi(optional)/Pocket LAN(optional)/Pocket GPRS(optional)/Meter(optional)/RS485/DRM/USB-Upgrade					
LCD display	Yes					
Standard warranty [years]	5-10					



X1-SMART (SINGLE PHASE)

	X1-6.0	X1-7.0	X1-8.0
INPUT (DC)			
Max.PV array power [Wp]	9000	10500	12000
Max.recommended DC power[W]	3000/4000	3000/5000	3000/6000
Max.DC voltage [V]	550	550	550
Nominal DC operating voltage [V]	360	360	360
Max. input current [A]	12/24	12/24	12/24
Max. short circuit current [A]	14/28	14/28	14/28
MPPT voltage range[V]	100-530	100-530	100-530
Start operating voltage[V]	120	120	120
No. of MPPT trackers/Strings per MPPT tracker	2(1/2)	2(1/2)	2(1/2)
OUTPUT AC			
Nominal AC power [VA]	6000	7000	8000
Max. AC power [VA]	6600	7700	8800
Nominal grid voltage(AC voltage range) [V]	220/230/240; 160-285		
Nominal grid frequency/range [Hz]	50/60; ±5		
Nominal AC current [A]	28.7	33.5	38.3
Max. AC current [A]	45		
Displacement power factor	0.8 leading... 0.8 lagging		
THDi, rated power [%]	< 3		
EFFICIENCY			
MPPT efficiency [%]	99.90		
Euro efficiency [%]	96.80		
Max. efficiency [%]	97.40		
POWER CONSUMPTION			
Standby consumption (Night) [W]	<1		
STANDARD			
Over voltage protection	YES		
Over current protection	YES		
DC isolation impedance monitoring	YES		
Ground fault current monitoring	YES		
DC injection monitoring	YES		
RCD protection	YES		
Safety	IEC62109-1/IEC62109-2		
EMC	EN 61000-3-2 / EN 61000-3-3 / EN 61000-3-11 / EN 61000-3-12 / EN 61000-6-1 / EN 61000-6-2 / EN 61000-6-3		
Certification	AS4777		
ENVIRONMENT LIMIT			
Degree of protection(according to IEC60529)	IP65		
Operating temperature range [°C]	-25~+60 (derating at 45)		
Max. operation altitude [m]	<2000		
Humidity [%]	0~100 (condensing)		
Storage temperature [°C]	-25~+60		
Typical noise emission [dB]	<40		
DIMENSION AND WEIGHT			
Dimensions(WxHxD) [mm]	401*450*190		
Weight[kg]	22		
Cooling concept	Natural		
Topology	Non-isolated		
Communication interfaces	Pocket WiFi(optional)/Pocket LAN(optional)/Pocket GPRS(optional)/Meter(optional)/RS485/DRM/USB-Upgrade		
LCD display	Backlight 20*4 character		
Standard warranty [years]	5-10		



X3-MIC (THREE PHASE) *(T For Dual MPPT S For Single MPPT)*

	X3-4.0-T	X3-5.0-T	X3-6.0-T	X3-7.0-T	X3-8.0-T	X3-9.0-T	X3-10.0-T	X3-4.0-S	X3-5.0-S
INPUT (DC)									
Max.PV array power [Wp]	6000	7500	9000	10500	12000	13500	15000	6000	7500
Max.recommended DC power[W]	6600/6600	6600/6600	6600/6600	6600/6600	6600/6600	6600/6600	6600/6600	6600	6600
Max.DC voltage [V]	800	800	800	1000	1000	1000	1000	1000	1000
Nominal DC operating voltage [V]	600	600	600	600	600	600	600	600	600
Max. input current [A]	12/12	12/12	12/12	12/12	12/12	12/12	12/12	12	12
Max. short circuit current [A]	14/14	14/14	14/14	14/14	14/14	14/14	14/14	14	14
MPPT voltage range[V]	160-750	160-750	160-750	160-900	160-900	160-900	160-900	160-900	160-900
Start operating voltage[V]	180	180	180	180	180	180	180	180	180
No. of MPPT trackers/Strings per MPPT tracker	2(1/1)	2(1/1)	2(1/1)	2(1/1)	2(1/1)	2(1/1)	2(1/1)	1	1
OUTPUT AC									
Nominal AC power [VA]	4000	5000	6000	7000	8000	9000	10000	4000	5000
Max. AC power [VA]	4400	5500	6600	7700	8800	9900	11000	4400	5500
Nominal grid voltage(AC voltage range) [V]	3/N/PE, 3/PE, 230/400(310-480)						3/N/PE, 3/PE, 230/400(310-480)		
Nominal grid frequency/range [Hz]	50/60;±5						50/60;±5		
Nominal AC current [A]	5.8	7.2	8.7	10.1	11.6	13.0	14.5	5.8	7.2
Max. AC current [A]	6.4	8.0	9.6	11.2	12.8	14.3	15.9	6.4	8.0
Displacement power factor	0.8leading-0.8lagging						0.8leading-0.8lagging		
THDi, rated power [%]	<2						<2		
EFFICIENCY									
MPPT efficiency [%]	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
Euro efficiency [%]	97.8	97.8	97.8	98	98	98	98	97.8	97.8
Max. efficiency [%]	98.3	98.3	98.3	98.4	98.4	98.5	98.5	98.3	98.3
POWER CONSUMPTION									
Standby consumption (Night) [W]	<3						<3		
STANDARD									
Over voltage protection	YES						YES		
Over current protection	YES						YES		
DC isolation impedance monitoring	YES						YES		
Ground fault current monitoring	YES						YES		
DC injection monitoring	YES						YES		
RCD protection	YES						YES		
Safety	EN62109-1/-2						EN62109-1/-2		
EMC	EN61000-6-1;EN61000-6-2;EN61000-6-3;EN61000-3-2;EN61000-3-3						EN61000-6-1;EN61000-6-2;EN61000-6-3;EN61000-3-2;EN61000-3-3		
Certification	AS4777; VDE4105; G98; G99; EN50549; CEI0-21						AS4777; VDE4105; G98; G99; EN50549; CEI0-21		
ENVIRONMENT LIMIT									
Degree of protection(according to IEC60529)	IP65						IP65		
Operating temperature range [°C]	-25~+60(derating at 45)						-25~+60(derating at 45)		
Max. operation altitude [m]	<2000						<2000		
Humidity [%]	0~100 (condensing)						0~100 (condensing)		
Storage temperature [°C]	-25~60						-25~60		
Typical noise emission [dB]	<35						<35		
DIMENSION AND WEIGHT									
Dimensions(WxHxD) [mm]	534*419*201						534*419*201		
Weight[kg]	30	30	30	30	30	30	30	28	28
Cooling concept	Natural						Natural		
Topology	Non-isolated						Non-isolated		
Communication interfaces	RS485/DRM/Pocket WiFi(optional)/Pocket LAN (optional)/Pocket GPRS (optional)/Meter (optional)/USB-upgrade						RS485/DRM/Pocket WiFi(optional)/Pocket LAN (optional)/Pocket GPRS (optional)/Meter (optional)/USB-upgrade		
LCD display	Backlight 16*4 character						Backlight 16*4 character		
Standard warranty [years]	5-10						5-10		



Features:

- Secure & reliable with software and hardware protection
- Maximum efficiency up to 98.3%, Euro efficiency up to 97.8%
- Wide MPPT voltage range & Two independent MPPT (three strings)
- Enclosure Rating-IP65
- Multiple protections: Over voltage / under voltage, earth protection, anti-islanding, overload, over temperature and RCD protection, etc.



X3-PRO (THREE PHASE)

X3-8.0P

X3-10.0P

X3-12.0P

X3-15.0P

INPUT (DC)

Max.PV array power [Wp]	12000	15000	18000	22500
Max.recommended DC power[W]	A:3200/B:6400	A:4000/B:8000	A:4800/B:9600	A:6000/B:12000
Max.DC voltage [V]	1000	1000	1000	1000
Nominal DC operating voltage [V]	600	600	600	600
Max. input current [A]	12/24	12/24	12/24	12/24
Max. short circuit current [A]	14/28	14/28	14/28	14/28
MPPT voltage range[V]	160-850	160-850	160-850	160-850
Start operating voltage[V]	180	180	180	180
No. of MPPT trackers/Strings per MPPT tracker	2(1/2)	2(1/2)	2(1/2)	2(1/2)

OUTPUT AC

Nominal AC power [VA]	8000	10000	12000	15000
Max. AC power [VA]	8800	11000	13200	16500
Nominal grid voltage(AC voltage range) [V]	3/N/PE, 230/400(310-480)			
Nominal grid frequency/range [Hz]	50/60;±5			
Nominal AC current [A]	11.6	14.5	17.4	21.7
Max. AC current [A]	12.8	15.9	19.1	23.9
Displacement power factor	0.8leading-0.8lagging			
THDi, rated power [%]	<3			

EFFICIENCY

MPPT efficiency [%]	99.9
Euro efficiency [%]	97.8
Max. efficiency [%]	98.3

POWER CONSUMPTION

Standby consumption (Night) [W]	<3
---------------------------------	----

STANDARD

Over voltage protection	YES
Over current protection	YES
DC isolation impedance monitoring	YES
Ground fault current monitoring	YES
DC injection monitoring	YES
RCD protection	YES
Safety	EN62109-1/-2
EMC	EN61000-6-1;EN61000-6-2;EN61000-6-3; EN61000-3-12; EN61000-3-11
Certification	VDE4105; AS4777; EN50549; IEC61727

ENVIRONMENT LIMIT

Degree of protection(according to IEC60529)	IP65
Operating temperature range [°C]	-25~+60(derating at 45)
Max. operation altitude [m]	<2000
Humidity [%]	0~100 (condensing)
Storage temperature [°C]	-25~60
Typical noise emission [dB]	<45

DIMENSION AND WEIGHT

Dimensions(WxHxD) [mm]	534*419*179
Weight[kg]	32
Cooling concept	Forced airflow
Topology	Non-isolated
Communication interfaces	RS485/DRM/Pocket WiFi(optional)/Pocket LAN (optional)/Pocket GPRS (optional)/Meter (optional)/USB-upgrade
LCD display	Backlight 16*4 character
Standard warranty [years]	5/10(optional)