

# **Energy Meter**

DDSU666

User Manual

Please read this manual carefully before use.

## **Notes and Safety**



Cut off all power of inverter before installation!
Wait for 5 minutes after power off.




Danger of high voltage!
Danger to life due to high voltage of this machine!

1 Basic features

DDSU666 Meter can achieve energy management together with solax single phase inverter.It applies to 60A system on below, measure the import, export and total power and energy.



## ② Terminals and Dimension




1,2,3	Single phase input port
7,8	RS485 port




① Mounting

DDSU666 meter is designed for indoor installation ,It could be installed on the wall or other place indoor.



②Wiring diagram





Direct access to the instrument



www.solaxpower.com

01

04

614.00341.00


③ Wiring Connection

Step 1: RS485 terminal connection 1. Prepare a communication cable.

- Trip the insulation from the communication cable.
   Connect the meter communication cable and inverter with reference to the inverter manual.
- 4.Connect the other end of the communication cable to the port 7 and 8 of meter. See the figure below for the connection.


Please note that the same color communication cable is used for the same communication port identifier between the inverter and the meter.

PS: The color of the communication cable in the figure is for reference only. Please refer to the actual situation for the specific connection.



### Step 2: Current wire connection

- 1.Insert the L wires to the ports 1 and 2 of the meter respectively. Connect port 1 with Grid terminal and port 2 with Load terminal.
- 2.Connect N wires with the port 3 of the meter.



#### LCD descript



Meaning that the meter is showing the voltage, the unit is 'V'



Meaning that the meter is showing the current, the unit is 'A'



Meaning that the meter is showing the active power, the unit is 'W'



Meaning that the meter is showing the active energy, the unit is 'A'



Meaning that the meter is showing the 645 communication protocol



Meaning that the current 645 address is 100000000011



Meaning that the current 645 address is 100000000011



Meaning that the baud rate is 2400

## Warranty Regulation

### Terms and conditions

SolaX grants a warranty of 12 months as standard. Starting from the date of the purchase invoice marked. SolaX will only perform warranty service when the faulty unit is returned to SolaX together with a copy of invoice and warranty card which were issued by the dealer and manufacturer to the users. In addition,the type label of the unit must be fully legible. If these requirements are notfulfille SolaX reserves the right for all warranty terms and conditions.

#### Exclusion of liability

Warranty claims are excluded for direct or indirect damage due to:

1: Use of unit in ways not intended, improper installation and installation thatdoes not comply with standards, improper operation and unauthorized modification to the units or epair attempt.

- 2: Without warranty card and serial number.
- 3: Operating the units with defective protective equipment.
- 4: Influence of oeign objects and force majeure.
- 5: Inadequate ventilation.
  6: Violate relevant safety regulations.

To register your SolaX product, please mail this warranty card to:

ADD: Room 506 West Buliding A Sci. and Tech Park of Zhejiang University No.525, Xixi Road, Hangzhou Zhejiang Province China 310007

Tel: +86 571 56260011 Fax: +86 571 56075753
Email: service@solaxpower.com

Web: http://www.solaxpower.com/

Online warranty registration is available at http://www.solaxpower.com/en/warranty-registration/

## Warranty Registration Form

Name	Country				
Phone Number	Zip Code				
Email					
Address					
Product Serial Number					
Date of Commissioning					
Installation Company Name					

Date of Delive	y
Signature	

06