TÜV SÜD
Product Service

C E R T I F I C A T E

No. Z2 102627 0022 Rev. 02

Holder of Certificate: **DAS SOLAR CO., LTD.**
No. 43, South of Bailing Rd
324022 Quzhou City, Zhejiang Province
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:

TÜV SÜD
IEC 61730 IEC 61215 Photovoltaics
Safety tested / Production monitored

Additional Environmental Tests
Salt Mist Corrosion
IEC 61701

Product: **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**

Mono-Crystalline Silicon Photovoltaic Module

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.:   704062305416-02

Valid until: 2029-01-01

Date,   2024-01-04

(Zhulin Zhang)

TÜV®

C E R T I F I C A T E

No. Z2 102627 0022 Rev. 02

Model(s):

1)DAS-DH156PA-xxx, xxx=570 to 610 in step of 5;
2)DAS-DH144PA-xxx, xxx=510 to 565 in step of 5;
3)DAS-DH132PA-xxx, xxx=470 to 515 in step of 5;
4)DAS-DH120PA-xxx, xxx=425 to 470 in step of 5;
5)DAS-DH108PA-xxx, xxx=385 to 425 in step of 5;
6)DAS-DH156NA-xxx, xxx=585 to 635 in step of 5;
7)DAS-DH144NA-xxx, xxx=530 to 590 in step of 5;
8)DAS-DH132NA-xxx, xxx=485 to 540 in step of 5;
9)DAS-DH120NA-xxx, xxx=445 to 490 in step of 5;
10)DAS-DH108NA-xxx, xxx=400 to 440 in step of 5;
11)DAS-DH144ND-xxx, xxx=580 to 615 in step of 5;
12)DAS-DH108ND-xxx, xxx=435 to 460 in step of 5;
xxx is standing for rated output power at STC

Parameters:

Construction:	Framed, with Junction box, Cable and Connectors.
Safety Class:	Class II
Fire Safety Class:	Class C according to UL790
Maximum System Voltage:	1500 V DC
Test method of salt mist test:	test method 8 (180 Cycles)

Tested according to:

IEC 61215-1:2016
IEC 61215-1-1:2016
IEC 61215-2:2016
IEC 61730-1:2016
IEC 61730-2:2016
IEC 61701:2020